

HEAVY DUTY

ELETRICO / ELECTRIC



# K 5000 - 6000 - 7000 - 8000 - 9000



## ACCESSORI STANDARD STANDARD ACCESSORIES



920mm

Lancia con pistola automatica da 920 mm.  
920 mm. lance with automatic trigger gun

**10** Tubo alta pressione da 10 metri  
10 meters high pressure hose

Dimensioni tubo / Hose dimensions

**R2 3/8**

5000 - 6000 - 7000 - 8000 - 9000

## CARATTERISTICHE FEATURES



**SBS**  
STAND-BY STOP



**TST**  
TOTAL STOP



**WATER LEAK**



**TVS**  
THERMAL VALVE SYSTEM

## IMBALLAGGIO / PACKAGING



120x70x105 cm



125 kg

## CARATTERISTICHE / FEATURES

Modello Model	Portata Flow Rate lt/min	Pressione / Pressure		Pompa / Pump		Potenza / Power		Tensione Voltage Volts	Frequenza Frequency Hertz	Fase Phase	Codice Code
		Bar	Bar	rpm	rpm	HP	kW				
<b>K5000</b>	21	200	200	1450	1450	10	7.5	400 V	50	3	3.023.14.393
<b>K6000</b>	30	200	200	1450	1450	15	11	400 V	50	3	3.023.14.386
<b>K7000</b>	40	150	150	1450	1450	15	11	400 V	50	3	3.023.14.387
<b>K8000</b>	14	400	400	1450	1450	15	11	400 V	50	3	3.023.14.388
<b>K9000</b>	18	300	300	1450	1450	15	11	400 V	50	3	3.023.14.389

Disponibile anche a 60Hz / Available at 60Hz

Versione FX su richiesta / Fx Model on demand

HEAVY DUTY

ELETRICO / ELECTRIC

# FX 5000 - 6000 - 7000 - 8000 - 9000



## FX5000-6000-7000-800-9000

Telaio in acciaio cromato su richiesta  
*Chrome-plated steel frame on demand*



## MOTORE / ENGINE



Motore elettrico MAZZONI senza manutenzione asincrono monofase serie MEC, con termiche sugli avvolgimenti.  
*MAZZONI MEC series maintenance-free electric induction motor with thermic protection on the windings*

Giunto elastico  
*Elastic coupling*

## POMPA / PUMP



Pompa professionale in linea (a bielle) con testata in ottone e tre pistoni in ceramica.  
*In line professional pump (with connecting rods), brass head, and three ceramic pistons.*

## CARATTERISTICHE TECNICHE / TECHNICAL FEATURES

- 1 Tanica detergente da 5 litri
- 2 Valvola by-pass regolabile
- 3 Valvola di sicurezza
- 4 Quadro elettrico ed interruttore on-off
- 5 Telaio in acciaio verniciato
- 6 Freno di stazionamento
- ✓ Contatore interno

*5 litres detergent tank*  
*Adjustable by-pass valve*  
*Safety valve*  
*Switchboard*  
*Painted steel frame*  
*Parking brake*  
*Internal hour meter*

## DETTAGLI / DETAILS



Freno di stazionamento  
*Parking brake*


## ACCESSORI OPZIONALI / OPTIONAL ACCESSORIES ● 5000 ● 6000 ● FX6000



3.020.22.055/62 ●  
 3.020.22.060 ● ● ●  
 Ugello rotativo / Turbo nozzle



3.061.04.002 ● ● ● ●  
 Lettore ore / Hours reader



3.020.22.022 ● - 3.020.22.066 ● ● ● ●  
 Kit sabbatura / Sandblasting Kit



2.071.04.008 > 10/20 mt ● ● ● ●  
 2.071.04.017 > 30/40 mt ● ● ● ●  
 Avvolgitubo / Hose reel



Accessoriata  
 Full Accessories

